


IT'S TIME FOR INTERNET OF THINGS

GSM POWER SOCKET 5G10A

GSMLIS-001



Power strip in Rack 19" standard equipped with 5 independently managed 230V sockets and GSM module for sockets remote control. Managing sockets can be performed via SMS messages with authentication password. Power GSM module is supported by the battery, so that the proper programming can be notified of the lack of power and return.

Sheets has an input for temperature sensors as standard 1wire (DS18B20). It is possible to support up to 4 sensors (on sale splitter 4 to 1).

Examples of applications:

- Server cabinets
- Low power heating control
- Power devices that require remote control
- Power devices requiring temporary on/off

Technical Specifications:

product code / name	GSMLIS-001 / GSM Power Socket 5G10A
Number of sockets	5
Supply voltage	AC 230 V
Maximum current	10 A
Maximum power	2300 W
Protection	2 x 10 A
Type of connection	cable with plug
Micro USB	1 piece
1wire	RJ11 RJ11 service to 4 sensors
Battery	12V 0,8Ah (back-up GSM)
Buffer power supply	Meanwell SCP-35-12, 13,8 V / 2,6 A
Dimensions (height x length x width)	45 x 425 x 140 mm (without handles)
Weight	2,60 kg

Features:

- management: USB console and SMS
- remote on/reset slots - SMS
- measurement of 4-ch temperature sensors 1wire
- the ability to set notifications of power failure.

tinycontrol.eu <...> **microprocessors projects**

Konsorcjum ATS Sp.j. 26-600 Radom, ul. Żeromskiego 75, POLAND
tel./fax +48 48 383 00 30, e-mail: sklep@wirelesslan.pl, info@ats.pl, www.tinycontrol.eu, www.wirelesslan.eu